

Source Code Highlight Filter

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME
8.6.1	22 August 2010		

Contents

1	Examples	1
1.1	Source code paragraphs	1
1.2	Unnumbered source code listing	1
1.3	Numbered source code listing with callouts	2
2	Installation	3
2.1	HTML	3
2.2	DocBook	3
2.3	Testing	4

The AsciiDoc distribution includes a source code syntax highlight filter (`source-highlight-filter.conf`). It uses **GNU source-highlight** to highlight HTML outputs. You also have the option of using the **Pygments** syntax highlighter for *xhtml11* outputs.

To use Pygments you need to define an AsciiDoc attribute named *pygments* (either from the command-line or in the global `asciidoc.conf` configuration file) and you will also need to have Pygments installed and the *pygmentize* command in your PATH. You can customize Pygments CSS styles by editing `./stylesheets/pygments.css`. To make Pygments your default highlighter put the following line your `~/asciidoc/asciidoc.conf` file:

DocBook outputs are highlighted by toolchains that have `programlisting` element highlight support, for example *dblatex*.

Tip

- If the source *language* attribute has been set (using an *AttributeEntry* or from the command-line) you don't have to specify it in each source code block.
 - You may need to place callout markers inside source code comments to ensure they are not misinterpreted and mangled by the highlighter.
-

1 Examples

1.1 Source code paragraphs

The `source` paragraph style will highlight a paragraph of source code. These three code paragraphs:

```
[source,python]
if n < 0: print 'Hello World!'

:language: python

[source]
if n < 0: print 'Hello World!'

[source,ruby,numbered]
[true, false].cycle([0, 1, 2, 3, 4]) do |a, b|
  puts "#{a.inspect} => #{b.inspect}"
```

Render this highlighted source code:

```
if n < 0: print 'Hello World!'
```

```
if n < 0: print 'Hello World!'
```

```
1 [true, false].cycle([0, 1, 2, 3, 4]) do |a, b|
2   puts "#{a.inspect} => #{b.inspect}"
```

1.2 Unnumbered source code listing

This source-highlight filtered block:

```
[source,python]
-----
''' A multi-line
    comment.'''
def sub_word(mo):
```

```
''' Single line comment.'''
word = mo.group('word')    # Inline comment
if word in keywords[language]:
    return quote + word + quote
else:
    return word
-----
```

Renders this highlighted source code:

```
''' A multi-line
    comment.'''
def sub_word(mo):
    ''' Single line comment.'''
    word = mo.group('word')    # Inline comment
    if word in keywords[language]:
        return quote + word + quote
    else:
        return word
```

1.3 Numbered source code listing with callouts

This source-highlight filtered block:

```
[source,ruby,numbered]
-----
#
# Useful Ruby base class extensions.
#

class Array

  # Execute a block passing it corresponding items in
  # +self+ and +other_array+.
  # If self has less items than other_array it is repeated.

  def cycle(other_array) # :yields: item, other_item
    other_array.each_with_index do |item, index|
      yield(self[index % self.length], item)
    end
  end

end

if $0 == __FILE__                                     <1>
  # Array#cycle test
  # true => 0
  # false => 1
  # true => 2
  # false => 3
  # true => 4
  puts 'Array#cycle test'                             <2>
  [true, false].cycle([0, 1, 2, 3, 4]) do |a, b|
    puts "#{a.inspect} => #{b.inspect}"
  end
end
-----

<1> First callout.
<2> Second callout.
```

Renders this highlighted source code:

```
1 #
2 # Useful Ruby base class extensions.
3 #
4
5 class Array
6
7   # Execute a block passing it corresponding items in
8   # +self+ and +other_array+.
9   # If self has less items than other_array it is repeated.
10
11   def cycle(other_array) # :yields: item, other_item
12     other_array.each_with_index do |item, index|
13       yield(self[index % self.length], item)
14     end
15   end
16
17 end
18
19 if $0 == __FILE__ ❶
20   # Array#cycle test
21   # true => 0
22   # false => 1
23   # true => 2
24   # false => 3
25   # true => 4
26   puts 'Array#cycle test' ❷
27   [true, false].cycle([0, 1, 2, 3, 4]) do |a, b|
28     puts "#{a.inspect} => #{b.inspect}"
29   end
30 end
```

- ❶ First callout.
- ❷ Second callout.

2 Installation

2.1 HTML

If you want to syntax highlight AsciiDoc HTML outputs (html4 and xhtml11 backends) you need to install [GNU source-highlight](#) or [Pygments](#) (most distributions have these packages).

2.2 DocBook

AsciiDoc encloses the source code in a DocBook *programlisting* element and leaves source code highlighting to the DocBook toolchain (dbletexp has a particularly nice programlisting highlighter). The DocBook programlisting element is assigned two attributes:

1. The *language* attribute is set to the AsciiDoc *language* attribute.
2. The *linenumbers* attribute is set to the AsciiDoc *src_numbered* attribute (*numbered* or *unnumbered*).

2.3 Testing

Test the filter by converting the test file to HTML with AsciiDoc:

```
$ asciidoc -v ./filters/source/source-highlight-filter-test.txt
$ firefox ./filters/source/source-highlight-filter-test.html &
```